

GPC100



Features

- . 10.4-19寸 便携加固机 单点/多点触控
- . 板载CPU DDR SSD
- . msata mini-pcie
- . 支持2.5硬盘

宽压输入: 9-24V DC_IN AC220

系统 System

处理器 Processor	Intel® Apollo Lake系列
内存 Memory	1 x DDR4 1866/2133MHz SO-DIMM, Up to 16 GB
图形 Graphics	Intel® HD Graphics , dual display
存储 Storage	1 x SATA 3.0 for 2.5" HDD/SSD 1 x mSATA,
操作系统 OS	Windows 7/8/10, Linux

外部接口 External I/O

网口 Ethernet	2 x RJ45 Intel® i211AT GbE (10/100/1000 Mbps)
显示 Video	1 x VGA: max resolution up to 1920 x 1200 1 x HDMI: max resolution up to 4096 x 2160
音频 Audio	1 x Audio(Line-out&Mic-in 2 in 1), Realtek® ALC269 HD Audio codec
串口 COM	6 x COM (2 x RS232/422/485 auto-flow, 4 x RS232)
USB	4 x USB 2.0, 1 x USB 3.0
GPIO	no
按钮 Button	1 x Power button
指示灯 LED	1 x Power LED (Green for Power-on, Blink for Sleep mode, Off for Power-off) 1 x HDD LED (Red blink for Data read or write)

内部接口 Internal I/O

扩展接口 Expansion	1 x Full-size Mini-PCIe Slot (co-lay with mSATA)
SIM卡	1 x SIM Card Slot
操作温度 OperatingTemp.	-20°C ~ 60°C(SSD), 0°C ~ 40°C(HDD)
存储温度 Storage Temp.	-40°C ~ 85°C
湿度 Relative Humidity	5% ~ 95%, 非凝结状态Non-condensing
振动 Vibration	SSD: 5~500Hz, 2Grms operation HDD: 5~500Hz, 1Grms operation
机械冲击 Shock	Operation: Non-operation: 30G@11ms

电源 Power

电源输入 Power Input	AC-220 9~24V DC, 2-pin phoenix onnector
外观 Housing	铝合金 Aluminum Alloy
尺寸 Dimension	
重量 Weight	0.6kg

GPC200



Features

- . 10.4-19寸 便携加固机 单点/多点触控
- . 板载CPU DDR SSD
- . SIM插槽 msata mini-pcie
- . 支持2.5硬盘
- . 宽压输入: 9-36V DC_IN AC220

系统 System

处理器 Processor	Intel® Core™ i3/i5/i7
内存 Memory	1 x DDR4 1866/2133MHz SO-DIMM, Up to 16 GB
图形 Graphics	Intel® HD Graphics
存储 Storage	1 x SATA 3.0 for 2.5" HDD/SSD 1 x mSATA, 1 x M.2 2242 Slot
操作系统 OS	Windows 7/8/10, Linux
看门狗定时器 Watchdog Timer	Programmable 255 levels timer interval, from 1~255 sec/min

外部接口 External I/O

网口 Ethernet	2 x RJ45 Intel® i211AT GbE (10/100/1000 Mbps)
显示 Video	1 x VGA: max resolution up to 1920 x 1200 1 x HDMI: max resolution up to 4096 x 2160
音频 Audio	1 x Audio(Line-out&Mic-in 2 in 1), Realtek® ALC269 HD Audio codec
串口 COM	6 x COM (2 x RS232/422/485 auto-flow, 4 x RS232/485 optional by jumper)
USB	4 x USB 2.0, 2 x USB 3.0
GPIO	1 x 8bit programmable GPIO
按钮 Button	1 x Power button
指示灯 LED	1 x Power LED (Green for Power-on, Blink for Sleep mode, Off for Power-off) 1 x HDD LED (Red blink for Data read or write)

内部接口 Internal I/O

扩展接口 Expansion	1 x Full-size Mini-PCIe Slot (co-lay with mSATA) 1 x M.2 2242 Slot 1 x M.2 2230 Slot for Wifi module
SIM卡	1 x SIM Card Slot
操作温度 OperatingTemp.	-20°C ~ 60°C(SSD), 0°C ~ 40°C(HDD)
存储温度 Storage Temp.	-40°C ~ 85°C
湿度 Relative Humidity	5% ~ 95%, 非凝结状态Non-condensing
振动 Vibration	SSD: 5~500Hz, 2Grms operation HDD: 5~500Hz, 1Grms operation
机械冲击 Shock	Operation: Non-operation: 30G@11ms

电源 Power

电源输入 Power Input	AC-220 9~36V DC, 2-pin phoenix onnector
外观 Housing	铝合金 Aluminum Alloy
尺寸 Dimension	
重量 Weight	1.9kg